


# SAFAVIEH

## L I G H T I N G

### Assembly Instruction

**CAUTION:** Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

**ITEM#:LIT4475 A/B**



### Care and Cleaning












To clean the outside of the fixture, use a dry or slightly dampened clean cloth(use clean water, never a solvent)to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the interior surface of the fixture.

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time:30 minutes

### Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	Mounting Plate		1X	G	Short tube w/ teeth		1X
B	Wire Nut		3X	H	Long tube		2X
C	Mounting Screw		2X	I	Hook		1X
D	Canopy		1X	J	Lamp Bobby		1X
E	Canopy Nut		2X	K	Bulb		12X
F	Short tube		1X				1X

# Installation

## Step 1


Unpack all parts from cartons carefully.

Insert the fixture wires through the Short Tube(F) and secure the Short tube (F) into the threaded nipple of the lamp body (J) as diagram until tight.

Insert the fixture wires through the Short Tube w/teeth(G) and secure it into the Short Tube(F) as diagram until tight.

Insert the fixture wires through the Long Tube(H) and secure it into the Short Tube w/teeth(G) as diagram until tight.

Insert the fixture wires through another Long Tube (H) and secure it into the Long Tube(H) downward as diagram until tight.




## Step 2

Insert the fixture wire through the Hook(I) and Canopy(D).


Insert the Hook(I) into the Long Tube(H) and rotate it clockwise till tight.

Insert the Hook(I) into the ring of the Canopy(D) as diagram.




## Step 3

Separate the Mounting Plate(A) from the Canopy(D) by removing the Canopy Nuts(E) anti-clockwise.




## Step 4

Attach the Mounting Plate (A) onto the junction box and fix it by inserting the Mounting Screws(C) clockwise till tight..



## Step 5 Wire connection

Connect,Hot,Black or Red outlet Supply Wire to:	Connect,Neutral,White Outlet Supply Wire to:
Black	White
*Parallel Cord(round&smooth)	*Parallel Cord(square&ridged)
Clear,Brown,Gold or Black without Tracer(colored stripes)	Clear,Brwn,Gold or Black without Tracer(colored stripes)
Insulated Wire(not green)with copper metal conductor	Insulated Wire(not green)with Silver metal conductor



\*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)

### Grounding Instructions:


- For installation in the United States: Wrap ground wire from outlet box around green ground screw (F) on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.
- For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.

## Step 6

Attach the Canopy(D) over the Mounting Plate (A) and fix it by turning the Canopy Nuts(E) clockwise till tight.

Insert the bulbs(K) into the sockets of the Lamp body until secure. DO NOT EXCEED THE SPECIFIED WATTAGE.

**PLEASE USE TYPE"A" BULB MAX 40-WATT OR EDISON BULB MAX 40-WATT OR CFL BULB MAX 13-WATT OR LED MAX 9-WATT**  
**THERE ARE 12\* EDISON 4-WATT BULBS IN THE BOX**



## Step 7

Consult a qualified electrician to ensure correct branch circuit conductor

**ENJOY YOUR LAMP**