


SAFAVIEH LIGHTING

Assembly Instruction

CAUTION: Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

ITEM#:PLT4038A-SET2



Care and Cleaning











To clean the outside of the fixture, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the interior surface of the fixture

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time:20 minutes

Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	machine screw		2X	F	rubber ring		2X
B	mounting screw		2X	G	Hexagon Nut		2X
C	mounting bracket		1X	H	bulb		1X
D	ground screw		1X	I	Glass shade		1X
E	wire connector		3X	J	Lamp body		1X

Installation


Step 1

Install the mounting bracket(C) to the junction box with machine screw (A)


Step 2 Wire connection

Make wire connections, with wire connectors(E), following the reference chart listed below.

Connect,Hot,Black or Red outlet Supply Wire to:	Connect,Neutral,White Outlet Supply Wire to:
Black	White
*Parallel Cord(round&smooth)	*Parallel Cord(square&ridged)
Clear,Brown,Gold or Black without Tracer(colored stripes)	Clear,Brwn,Gold or Black without Tracer(colored stripes)
Insulated Wire(not green)with copper metal conductor	Insulated Wire(not green)with Silver metal conductor



*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)



Grounding Instructions:

- a) For installation in the United States: Wrap ground wire from outlet box around green ground screw(D) on mounting bracket(C), no less than 2" from wire end. Tighten ground screw(D). If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector(E).
- b) For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket(C). Tighten ground screw(D).

Step 3

Attach the Canopy of the Lamp body(J) to the mounting bracket(C) , and secure with rubber rings(F) and screws(B) by turning the Hexagon nut (G) clockwise clockwise .


Step 4

Insert the bulbs (H) into the socket.

PLEASE USE TYPE"A" BULB MAX 25-WATT OR CFL BULB MAX 9-WATT OR LED BULB MAX 5-WATT
THERE ARE 1PCS LED 4-WATT BULB IN THE BOX

Step 5

Put the glass shade(I) on the lamp body(J) and fasten clockwise to fix it.



Step 6

Consult a qualified electrician to ensure correct branch circuit conductor.

ENJOY YOUR LAMP