



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-641R1 - LED Adjustable High bay; 110 Watt; 4000K; Integrated Sensor Port; 120-277 Volt

- IC Rated



ELECTRICAL

Technology:	LED
Watts:	110W
Volts:	120V-277V
Lumens:	15871L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80+
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	100
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	200W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	330
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 4KV
THD:	20%
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923656170
Each Quantity:	1
Each Dimensions:	30.12 x 15.16 x 4.72
Case UPC:	10045923656177
Case Quantity:	1
Case Dimensions:	30.12 x 15.16 x 4.72

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	L:26.00" W:12.00" H:1.88"
Weight (Lbs.):	7.72
Material:	Aluminum Alloy
Sensor:	Multiple Optional Sensors Available

INSTALLATION

Wire Quantity:	5
Wire Length:	5.91 in.
Wire Temperature:	105C (221F)

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-1Y9D3K
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
UL/ETL File Listing:	CN - E495551
UL/ETL Standard:	CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP40
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

ACCESSORIES



86-217 Add-On PIR Sensor White Finish/6 Meter



86-218 Add-On Microwave Sensor for High Bay Fixtures; Must Be Used With Remote 86-219



86-220 Add-On PIR Sensor; 12 Meter
