



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11863** - 15 Watt; CCT Selectable; LED Direct Wire Downlight;  
Gimbaled; 6 Inch Square; Remote Driver; Black

- Air Tight
- Has Driver
- CCT Selectable
- IC Rated



### ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1280L-1400L
CRI:	90
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	40
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Connection:	Direct Wired
Power Factor :	>0.9
Warranty:	5 Year Limited - LED Commercial Downlights

### PACKAGING

Each UPC:	045923118630
Each Quantity:	1
Each Dimensions:	8.11 x 3.94 x 8.19
Case UPC:	10045923118637
Case Quantity:	12
Case Dimensions:	16.85 x 12.48 x 17.09

### PHYSICAL

Finish:	Black
Lens Finish:	Clear
Lens Material:	Plastic
Finish Family:	Black
Dimensions:	L:7.48" W:7.48" H:2.17"
Material:	Aluminum

### INSTALLATION

Max Drywall Thickness:	1 in.
Rec. Spacing Between Fixtures:	3 ft. to 4 ft.
Clearance Height:	3
Sloped Ceiling Compatible:	Yes
Can Size:	6 in.

### COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Pending
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP42
RoHS Compliant:	Yes
Restrictions:	No Restrictions

## ACCESSORIES

---



**80-944**

6" Rough-In Remove Driver Mounting Plate

---



**80-951**

Rough-In Mounting Plate; 6" with Junction Box

---



**80-985**

6 Foot Remote Driver Extension Cable

---



**86-216**

Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts

---