



Project/Job Name:

Location:

Fixture Type:

Notes:

**S11390** - 4.5 Watt MR16 LED; Silver Finish; 5000K; GU5.3 Base; 360 Lumens; 12 Volt

- Rated for Enclosed Fixture



## ELECTRICAL

|                           |                                |
|---------------------------|--------------------------------|
| Technology:               | LED                            |
| Watts:                    | 4.5W                           |
| Volts:                    | 12V                            |
| Lumens:                   | 360L                           |
| CRI:                      | 80                             |
| CCT (Kelvins):            | 5000K                          |
| Temperature:              | Natural Light                  |
| Beam Spread :             | 15                             |
| Hours Rated:              | 25000                          |
| Dimmable:                 | Yes-Dimmable                   |
| DimmableText:             | 0-10V Dimming Only             |
| Dimming Type :            | Forward Phase or Reverse Phase |
| Incandescent Equivalent : | 35W                            |
| Operating Temperature :   | -25C (-13F) to +45C (+113F)    |
| Number of LEDs :          | 6                              |
| Power Factor :            | 0.94                           |
| Light Source:             | LED                            |
| CBCP :                    | 3000                           |
| Warranty:                 | 5 Year Limited - 10 hr per day |

## PACKAGING

|                   |                     |
|-------------------|---------------------|
| Each UPC:         | 045923113901        |
| Each Quantity:    | 1                   |
| Each Dimensions:  | 1.97 x 1.97 x 2.56  |
| Inner UPC:        | 20045923113905      |
| Inner Quantity:   | 12                  |
| Inner Dimensions: | 6.42 x 4.33 x 5.51  |
| Case UPC:         | 10045923113908      |
| Case Quantity:    | 48                  |
| Case Dimensions:  | 13.70 x 9.45 x 6.50 |

## PHYSICAL

|                |                                         |
|----------------|-----------------------------------------|
| ANSI Base:     | GU5.3                                   |
| Base:          | Bi Pin GU5.3                            |
| Shape:         | MR16                                    |
| Finish:        | Gray                                    |
| Lens Finish:   | Array                                   |
| Lens Material: | Plastic                                 |
| MOD (In.):     | 1.97                                    |
| MOL (In.):     | 1.77                                    |
| Weight (Lbs.): | 0.08                                    |
| Material:      | Metal / Plastic / Electronic Components |
| Housing Color: | Gray                                    |
| Lensed:        | Lensed Lamp                             |

## COMPLIANCE

|                             |                 |
|-----------------------------|-----------------|
| Safety Listing:             | cULus           |
| Location Rating:            | Damp            |
| Energy Star Qualified:      | No              |
| Rated For Enclosed Fixture: | Yes             |
| FCC Compliant:              | Yes             |
| RoHS Compliant:             | Yes             |
| Restrictions:               | No Restrictions |



**S11390** - 4.5 Watt MR16 LED; Silver Finish; 5000K; GU5.3 Base; 360 Lumens; 12 Volt

#### DIMMER COMPATIBILITY

---

|        |           |
|--------|-----------|
| Lutron | CTRP-253P |
| Lutron | DVLV-600P |
| Lutron | MA-PRO    |
| Lutron | NTLV-600  |
| Lutron | NTRP-250  |
| Lutron | SLV-600P  |