



ELECTRICAL

Technology:	LED	
Watts:	12W	
Volts:	120V	
Lumens:	840L	
CRI:	90	
R9 Value :	51	
CCT (Kelvins):	2700K/3000K/3500K/4000K/5	
	oooK	
Beam Spread :	40	
Hours Rated:	50000	
Dimmable:	Yes-Dimmable	
Dimmable Down To %:	100 to 20 percent	
Dimming Type :	Forward Phase or Reverse Phase	
	or Phase Selectable or Triac	
Incandescent Equivalent :	75W	
Operating Temperature :	-20C (-4F) to +45C (+113F)	
Replaceable Light Source :	No	
Number of LEDs :	12	
Connection:	Direct Wired	
THD:	<30%	
Power Factor :	>0.9	
Warranty:	5 Year Limited - Fixtures	
	-	

PACKAGING

Each UPC:	045923311277	
Each Quantity:	1	
Each Dimensions:	5.31 × 3.74 × 5.31	
Case UPC: 10045923		
Case Quantity:	12	
Case Dimensions:	12.20 × 11.42 × 11.61	

Project/Job Name:

Location:

Fixture Type:

Notes:

\$11624R1 - 12 Watt LED Direct Wire Downlight; Gimbaled; 3.5 Inch; CCT Selectable; Round; Remote Driver; White Finish; 840 Lumens; 120 Volt

• Air Tight

• CCT Selectable

• IC Rated











PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Poly methyl methacrylate
	(PMMA)
Finish Family:	White
Dimensions:	H:2.10" DIA:4.38"
Weight (Lbs.):	0.98
Material:	Aluminum

COMPLIANCE

Safety Listing:	cETLus - Listed	
Location Rating:	Wet	
Indoor/Outoor:	Indoor; Outdoor	
Energy Star Qualified:	Yes	
Energy Star Unique ID:	ESID-2684097	
Energy Star Lamp Category:	Downlight Recessed	
UL/ETL Standard:	ANSI/UL 1598; CSA-C22.2 No.	
	250.0	
CA Prop 65:	Lead	
FCC Compliant:	Yes	
RoHS Compliant:	Yes	
SDS Class:	LED_Lamp	
Restrictions:	No Restrictions	

INFO

Additional Info:	360 Degree Rotation: 30 Degree Tilt



S11624R1 - 12 Watt LED Direct Wire Downlight; Gimbaled; 3.5 Inch; CCT Selectable; Round; Remote Driver; White Finish; 840 Lumens; 120 Volt

ACCESSORIES

1 1 5 0	80-973	Emergency Driver Enclosure; For use with S8000 and S8002
LEO INDICATOR THAT EMPLOY FOR	80-987	Emergency Remote Test Switch; Single Gang Plate; White Finish
0000	S8000	5 Watt LED Emergency Driver; 120-277 Volts
	S8002	10 Watt LED Emergency Driver; 120-277 Volt