



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11881 - 15 Watt LED; Fire Rated; 6 Inch Direct Wire Directional Downlight; Round Shape; White Finish; CCT Selectable; Dimmable; 120 Volts

- Air Tight
- Has Driver
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1280L
CRI:	90
Rg Value :	51
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Color Description:	Warm White to Natural Light
Beam Spread :	40
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Number of LEDs :	40
Connection:	Direct Wired
THD:	<30%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923118814
Each Quantity:	1
Each Dimensions:	8.19 x 3.94 x 8.27
Case UPC:	10045923118811
Case Quantity:	12
Case Dimensions:	17.32 x 12.60 x 17.32

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Poly methyl methacrylate (PMMA)
Finish Family:	White
Dimensions:	H:2.17" DIA:7.48"
Weight (Lbs.):	1.57
Material:	Aluminum

INSTALLATION

Max Drywall Thickness:	1 in.
Rec. Spacing Between Fixtures:	3 ft. to 4 ft.
Clearance Height:	3
Sloped Ceiling Compatible:	Yes
Can Size:	6 in.

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2684099
Energy Star Lamp Category:	Downlight Recessed
UL/ETL Application:	Covered Ceiling Mount
UL/ETL Standard:	ANSI/UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

Additional Info:	2-Hour Fire Rated
Specification Note:	Rotation Angle 360 degrees; Tilt Angle 80 degrees

ACCESSORIES



80-944

New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter



80-947

6" Goof Ring for Remote Driver Installation



80-951

New Construction Mounting Plate for Stud/ Joist mounting of 6-inch Recessed Downlights; Up to 5.688-inch hole diameter



80-973

Emergency Driver Enclosure; For use with S8000 and S8002



80-985

6 FOOT REMOTE DRIVER 3-PIN EXT



80-987

Emergency Remote Test Switch; Single Gang Plate; White Finish



S8000

5 Watt LED Emergency Driver; 120-277 Volts



S8002

10 Watt LED Emergency Driver; 120-277 Volt