



Project/Job Name:

Location:

Fixture Type:

Notes:

S18802 - LED Retrofit Downlight; 5.5/6.5/8 Wattage Selectable; CCT and Lumens Selectable; 120 Volt; ColorQuick and PowerQuick Technology; Square; White Finish

- Wattage Selectable
- CCT Selectable
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	5.5W/6.5W/8W
Volts:	120V
Lumens:	500L/600L/700L
CRI:	90
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Number of LEDs :	24
Connection:	Connector or Adapter
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923188022
Each Quantity:	1
Each Dimensions:	5.51 x 3.35 x 5.51
Case UPC:	10045923188029
Case Quantity:	16
Case Dimensions:	14.37 x 11.81 x 11.81

INFO

Includes:	E26 Adapter included (S9001)
-----------	------------------------------

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	L:5.31" W:5.31" H:3.13"
Weight (Lbs.):	0.59
Material:	Aluminum ADC12

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2617816
Energy Star Lamp Category:	Downlight Solid State Retrofit
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions



S18802 - LED Retrofit Downlight; 5.5/6.5/8 Wattage Selectable; CCT and Lumens Selectable; 120 Volt; ColorQuick and PowerQuick Technology; Square; White Finish

ACCESSORIES



80-980 4 Inch Recessed Can; For New Construction



80-981 4 Inch Recessed Can; For Remodeling



S8999 GU24 Socket Adapter For Recessed Down Light



S9000 GU10 Socket Adapter For Recessed Down Light



S9538 4" Recessed Can; For New Construction



S9539 4" Recessed Can; For Remodeling
