



1.Assemble the big ring ①, firstly install the male and female connector ③, make sure the connector ③ tighten enough can not pull out anymore, and then put the split parts together, lock it with screw ④.(same step to install the small ring ②.)




2.Let the wire of small ring @ go through the short hanging tube @, hang the small ring @ to the big ring @ with hanging tube @.(Note: the wires of two rings can not meet at the same side.)

3.Let the wires of ring 1 and ring 2 go through the long hanging tubes 7, hang the fixture to the junction box 9 with tube 7.




4.Let the wires go through junction box ③ and connect all the wires by parallel with connectors ⑫(all live line-L use one connector, and neutral Line-N use another connector).

5.Let the wire go through top conver  $\circledR$  and hanging ring  $\circledR$ , rotate the ring ข to fix the cover v to the fixture.



6.Install the chain  $\ensuremath{\mathfrak{B}}$  to the fixture, let the wire go through the chain  $\ensuremath{\mathfrak{B}}.$ 



7.Install the bracket (4) to the ceiling junction box with screw (1).
8.Let the chain (3) and the wire go through ring (6) and canopy (5) and bracket (4), after that hang the fixture to the bracket with chain (3).
9.Connect the wire to your home line with cap connectors (8).
10.Rotate the ring (6) to lock the canopy (5) to the bracket.
11.Put the cylinder tube (9) on the bulb holder and install the bulb (20).

## D0154-8+4 / D0154-12+8

Please read carefully before installation!!!

Note: Please make sure that the electricity is powered off during installation!

Only a professional electrician should install this kind of product!