

screw ②

①

profile
D0130-6: 6PCS
D0130-8: 4PCS
D0130-12: 6PCS

- ⑥ grub screw 2pcs
- ⑦ hex key 1pcs
- ⑩ canopy 1pcs
- ⑪ cap nut 2PCS

- X 1PCS
- X 1PCS
- X 3PCS
- X 3PCS
- X 3PCS
- X 3PCS

④ end cap

⑤ screw 1PCS

③ hanging tube 1PCS

ball

light arm

⑧ light fixture 1PCS

⑨ chain 1PCS

note: profile A should connect with profile A,
profile B should connect with profile B...

1. Install the profile ① to a ring, and lock it with screw ②.

cut out the tie with scissors

ball

light arm

2. Negative spin the light arm 7-8 rounds and rotate to install it to the ball of the light fixture ⑧.

3. Let the wire of the fixture go through the hanging tube ③, rotate to install the tube ③ on the ball and lock it with grub screw ⑥ by hex key ⑦.

press the end to adjust the length of the string.

4. Rotate to install the end cap ④ on the thread rod of the ring ①, adjust the height of the string.

5. Connect the fixture ③ to the canopy ⑩ with chain ⑨, let the wire go through the chain ⑨ and canopy ⑩.

Loosen screw ⑤ and make the tube ③ straight, after that tighten the screw again

6. Install the bracket to the ceiling junction box with screw ⑫.

7. Connect the wire to your home line.

8. Install the fixture to the bracket with cap nut ⑪.

9. Install the bulbs ⑭.

D0130-6 / D0130-8 / D0130-12 / D0130L-12

Please read carefully before installation!!!

Note : Please make sure that the electricity is powered off during installation !

Only a professional electrician should install this kind of product !