




- 1. Open the light arms like picture showed.
- 2.Let the wire of the fixture 1 go through the hanging tube 2, rotate to fix tube 2 to the light fixture 1.
- 3.Let the hole of the plate which on the hanging tube  $\ @$  face to the bulbholder, after that use hex key  $\ @$  to rotate the grub screw  $\ @$  to fix the tube  $\ @$  on the light fixture  $\ @$ .




4.Hang the fixture to the canopy  $\, \textcircled{6} \,$  with chain  $\, \textcircled{5} ,$  let the wire go through chain  $\, \textcircled{5} \,$  and canopy  $\, \textcircled{6} .$ 



- 5.Install the bracket to the ceiling junction box with screw ⑦.
- 7.Install the light fixture to the bracket with cap nuts ⑥.
- 8.Put the glass dish 10 and cylinder tube 9 on the bulbholder.



9.Hang the crystal 1 to the small hole of light arm.. 10.Hang the crystal chain 1 to the light fixture 1.



11.Hang the crystal chain (3) between the light fixture (1) and the glass dish (10).

12. Hang the crystal chain (11) to the metal ring of crystal chain (11).

13.Install the bulb (14).

## D6017-4

Please read carefully before installation!!!

Note: Please make sure that the electricity is powered off during installation!

Only a professional electrician should install this kind of product!