



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-980** - 8.5 Inch LED Field Selectable Canopy Fixture; 25/30/40 Watts; 3K/4K/5K CCT

- Wattage Selectable
- CCT Selectable



## ELECTRICAL

Technology:	LED
Watts:	25W/30W/40W
Volts:	120V-277V
Lumens:	3125L-5400L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Color Description:	Soft White to Natural Light
Beam Spread :	150
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming
Incandescent Equivalent :	150W/250W
HID Equivalent :	52W/71W/90W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Direct Wired
Surge Protection :	Built-in surge protection - 6KV
THD:	10.20%
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

## PACKAGING

Each UPC:	045923659461
Each Quantity:	1
Each Dimensions:	10.39 x 5.04 x 10.51
Case UPC:	10045923659468
Case Quantity:	6
Case Dimensions:	21.46 x 15.83 x 11.42

## INFO

Additional Info:	UV stabilized powder coated finish
------------------	------------------------------------

## PHYSICAL

Finish:	Bronze
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Finish Family:	Bronze
Dimensions:	L:8.50" W:8.50" H:3.27"
Weight (Lbs.):	3.35
Material:	Die-cast Aluminum
Sensor:	No

## COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-4CXTMX
DLC Primary Use:	Parking Garage Luminaires
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
B.U.G Rating:	B2-U3-G2
Restrictions:	No Restrictions



**65-980** - 8.5 Inch LED Field Selectable Canopy Fixture; 25/30/40 Watts; 3K/4K/5K CCT

## ACCESSORIES

---



**65-150**

Add on Emergency Backup Battery for LED Square Canopy Light Fixtures; 9 Watt; 90 min. Run Time; Bronze Finish

---