

Project Name

Location

Prepared By



# SATCO S12263

3.5R14/LED/950/E26/120V

## Notes

[www] 06-17-2024 00:55:57

## General

|                         |               |
|-------------------------|---------------|
| Status                  | Active        |
| Watts                   | 3.5W          |
| Incandescent Equivalent | 40W           |
| Volts                   | 120V          |
| Shape                   | R14           |
| Base                    | Medium        |
| ANSI Base               | E26           |
| Finish                  | Frost         |
| CCT (Kelvin)            | 5000K         |
| Temperature             | Natural Light |
| CRI                     | 90            |
| Lumens                  | 300L          |
| Beam Spread             | 110           |
| Dimmable                | Yes-Dimmable  |
| Hours Rated             | 25000         |
| Technology              | LED           |

## Electrical

|                       |                             |
|-----------------------|-----------------------------|
| Operating Frequency   | 60Hz                        |
| CBCP                  | 90                          |
| Candlepower           | 90                          |
| Power Factor          | 0.9                         |
| Operating Temperature | -25C (-13F) to +45C (+113F) |

## Physical

|               |                    |
|---------------|--------------------|
| MOL           | 2.17               |
| MOD           | 1.78               |
| Lens Finish   | Frost              |
| Lens Material | Polycarbonate (PC) |
| Weight (lb.)  | 0.06               |

## Additional Information

|                            |                                |
|----------------------------|--------------------------------|
| Rated For Enclosed Fixture | Yes                            |
| Warranty                   | 5 Year Limited - 10 hr per day |

## Compliance

|                        |                 |
|------------------------|-----------------|
| Safety Listing         | cULus           |
| Location Rating        | Damp            |
| CA T20 / T24 Rationale | T20/T24 Pending |
| RoHS Compliant         | Yes             |
| FCC Compliant          | Yes             |