


your global source for unique lighting + home decor





your global source for unique lighting + home decor

READ & SAVE INSTALLATION & OPERATION INSTRUCTIONS

TOOLS & MATERIALS REQUIRED

Flat-blade screwdriver Philips head screwdriver Wire cutters

Wiring supplies as required by electrical code

CAUTION: Before assembling your Lighting fixture, refer to the section titled ELECTRICAL CONNECTIONS. If you feel you do not have electrical wiring experience, refer to a do-it yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

GENERAL

- 1. To ensure the success of the installation, be sure to read these instructions and review the diagrams before beginning
- 2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
- 3. These fixture are intended to be mounted to a 4" x 4" x 2-1/8" deep metal octagon outlet box. The box must be directly supported by the building structure.
- 4. Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Turning the power off by using the light switch is not sufficient to prevent electrical shock.
- 5. Clean with a dry cloth, Use no solvents or abrasives. Avoid dampness on all electrical components.

PREPARE THE FIXTURE NOTE: FIRST TURN OFF ELECTRICITY

Refer to the illustration of fixture parts and assembly.

- 1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
- 2. Fasten the mounting bracket to the outlet box using the two screws and plastic anchors supplied.

FINAL ASSEMBLY

- 1. Place the canopy against the mounting surface and attach the canopy to the mounting bracket using the canopy screws provided.
- 2. Attach the shade to the threaded stem of the electric holder in the following order
- $S1 \rightarrow \text{plastic holder ring} \rightarrow S2 \rightarrow \text{metal holder ring}$ (As per Drawing)
- 3. Install bulb (not included).
- 4. Restore electricity and check the operation of your lighting fixture.

IMPORTANT SAFETY INSTRUCTIONS

CAUTION: THIS PORTABLE LUMINAIRE HAS A POLARIZED PLUG (ONE BLADE IS WIDER THAN THE OTHER) AS A FEATURE TO REDUCE THE RISK OF ELECTRIC SHOCK. THIS PLUG WILL FIT IN A POLARIZED OUTLET ONLY ONE WAY. IF THE PLUG DOES NOT FIT FULLY IN THE OUTLET, REVERSE THE PLUG. IF IT STILL DOES NOT FIT, CONTACT A QUALIFIED ELECTRICIAN. NEVER USE WITH AN EXTENSION CORD UNLESS PLUG CAN BE FULLY INSERTED. DO NOT ALTER THE PLUG.

