



Project/Job Name:

Location:

Fixture Type:

Notes:

62-2407 - Kenzo; LED 1 Light Wall Sconce; Vintage Brass Finish; Light Guide Panel









ELECTRICAL

Watts: 6W Volts: 120V Lumens: 480L Lamp Base : Integrated - Integrated CRI: 90 Rg Value : 90 CCT (Kelvins): 3000K - Soft White Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +60C (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15% Power Factor : >0.9 Voltage Type: AC Only Warranty: 3-Years	Technology:	LED
Lumens: 480L Lamp Base : Integrated - Integrated CRI: 90 Rg Value : 90 CCT (Kelvins): 3000K - Soft White Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +6oC (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	Watts:	6W
Lamp Base: CRI: 90 Rg Value: 90 CCT (Kelvins): Beam Spread: Hours Rated: Dimmable: Dimmable: Dimmable Down To %: Incandescent Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: No THD: Power Factor: Ves-Dimmable 120 120 13000 120 120 120 120 1	Volts:	120V
CRI: 90 Rg Value : 90 CCT (Kelvins): 3000K - Soft White Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +60C (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	Lumens:	480L
Rg Value : 90 CCT (Kelvins): 3000K - Soft White Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +60C (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	Lamp Base :	Integrated - Integrated
CCT (Kelvins): 3000K - Soft White Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +6oC (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	CRI:	90
Beam Spread : 120 Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +6oC (+14oF) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	Rg Value :	90
Hours Rated: 30000 Dimmable: Yes-Dimmable - Dimmable Down To %: 100 to 10 percent Dimming Type : Triac Incandescent Equivalent : 48W Operating Temperature : -20C (-4F) to +6oC (+140F) Lamp Included : Integrated Replaceable Light Source : No THD: <15%	CCT (Kelvins):	3000K - Soft White
Dimmable: Dimmable Down To %: Dimmable Down To %: Dimming Type: Incandescent Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: THD: Yes-Dimmable - 100 to 10 percent 48W Operating Type: -20C (-4F) to +6oC (+140F) Integrated Replaceable Light Source: No THD: <15% Power Factor: >0.9 Voltage Type: AC Only	Beam Spread :	120
Dimmable Down To %:100 to 10 percentDimming Type :TriacIncandescent Equivalent :48WOperating Temperature :-20C (-4F) to +60C (+140F)Lamp Included :IntegratedReplaceable Light Source :NoTHD:<15%	Hours Rated:	30000
Dimming Type: Incandescent Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: THD: Power Factor: Voltage Type: Triac 48W -20C (-4F) to +6oC (+14oF) Integrated No 115% -20C (-4F) to +6oC (+14oF) -20C (-4F) to +6oC (Dimmable:	Yes-Dimmable -
Incandescent Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: THD: Power Factor: Voltage Type: AC Only	Dimmable Down To %:	100 to 10 percent
Operating Temperature :-20C (-4F) to +60C (+140F)Lamp Included :IntegratedReplaceable Light Source :NoTHD:<15%	Dimming Type :	Triac
Lamp Included : Integrated Replaceable Light Source : No THD: <15%	Incandescent Equivalent :	48W
Replaceable Light Source : No THD: <15%	Operating Temperature :	-20C (-4F) to +60C (+140F)
THD: <15% Power Factor: >0.9 Voltage Type: AC Only	Lamp Included :	Integrated
Power Factor: >0.9 Voltage Type: AC Only	Replaceable Light Source :	No
Voltage Type: AC Only	THD:	<15%
	Power Factor :	>0.9
Warranty: 3-Years	Voltage Type:	AC Only
	Warranty:	3-Years

PACKAGING

Each UPC:	045923407413
Each Quantity:	1
Each Dimensions:	11.42 x 10.63 x 8.27

PHYSICAL

Finish:	Polished Anodized Bronze
Lens Finish:	Clear
Lens Material:	Acrylic
Dimensions:	W:7.63" H:5.70" E:8.50"
Weight (Lbs.):	0.9
Material:	Aluminum / Steel
Number of Shades:	1

INSTALLATION

Sloped Ceiling Compatible:	No
Cord Length:	7 in.
Wire Length:	7 in.

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Damp
Indoor/Outoor:	Indoor
CA Prop 65:	Lead
BAA Compliant:	No
ADA Compliant:	No
FCC Compliant:	Yes
IK Rating:	IK01
RoHS Compliant:	Yes
Restrictions:	No Restrictions