



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

60-8669 - Solara; 6 Light Island Pendant; Natural Brass Finish;
Frosted Ribbed Glass



ELECTRICAL

| | |
|----------------------------|------------------|
| Technology: | Lamp Dependent |
| Watts: | 60W |
| Volts: | 120V |
| Lumens: | Lamp Dependent |
| Lamp Base : | E26 - Medium |
| Lamp Shape : | A19 |
| CRI: | Lamp Dependent |
| CCT (Kelvins): | Lamp Dependent - |
| Dimmable: | Lamp Dependent - |
| Lamp Included : | No |
| Number of Lamps : | 6 |
| Replaceable Light Source : | Yes |
| Lamp Watts : | 60W |
| Connection: | Hardwire |
| Voltage Type: | AC Only |
| Warranty: | 1-Year |

PACKAGING

| | |
|------------------|----------------------|
| Each UPC: | 045923408588 |
| Each Quantity: | 1 |
| Each Dimensions: | 41.73 x 13.39 x 8.27 |

INFO

| | |
|-----------|-------------------------------------|
| Includes: | (2) 6 Inch Stems; (2) 12 Inch Stems |
|-----------|-------------------------------------|

PHYSICAL

| | |
|-------------------|---------------------------|
| Finish: | Natural Brass |
| Dimensions: | L:40.00" W:12.00" H:7.13" |
| Height Max: | 44.01 |
| Weight (Lbs.): | 8.38 |
| Material: | Steel / Glass |
| Glass Finish: | Frosted Ribbed |
| Number of Glass: | 6 |
| Number of Shades: | 6 |
| Shade Dimensions: | D:3.74 H:5.12 |

INSTALLATION

| | |
|----------------------------|---------|
| Rod Length: | 36 in. |
| Sloped Ceiling Compatible: | Yes |
| Wire Length: | 144 in. |

COMPLIANCE

| | |
|------------------|-----------------|
| Safety Listing: | cETLus |
| Location Rating: | Dry |
| Indoor/Outdoor: | Indoor |
| CA Prop 65: | Lead |
| BAA Compliant: | No |
| FCC Compliant: | Yes |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |



60-866g - Solara; 6 Light Island Pendant; Natural Brass Finish;
Frosted Ribbed Glass

ACCESSORIES

| | |
|-------------------|---------|
| Glass 1: | 25-8641 |
| 6 Inch Stem: | 25-6841 |
| 6 Inch Stem Qty: | 1 |
| 12 Inch Stem: | 25-6842 |
| 12 Inch Stem Qty: | 1 |