


Assembly Instruction

<u>CAUTION</u>: Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

ITEM#:LIT4372A



Care and Cleaning

To clean the outside of the fixture, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth(use clean water, never a solvent) to wipe the interior surface of the fixture

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time:30 minutes

Part List and Hardware List


PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
А	mounting bracket		1X	G	chain	P	1X
В	mounting screw		2X	Н	flying rings		1X
С	mounting screw	ार्गुकवर्गुक	2X	I	ring	1	1X
D	wire connector		3X	J	bulb		3X
E	Collar loop	8	1X				
F	canopy		1X				

Installation

Step 1


Unpack all parts from cartons carefully.

1. Fix the flying ring (H) to ring (I)




Step 2

Fix collar loop(E) to mounting bracket(A), Fix mounting screw(B) to ceiling though mounting bracket (A)



Step 3 Wire connection

Connect,Hot,Black or Red outlet Supply Wire to:	Connect,Neutral,White Outlet Supply Wire to:		
Black	White		
*Parallel Cord(round&smooth)	*Parallel Cord(square&ridged)		
Clear,Brown,Gold or Black without Tracer(colored stripes)	Clear,Brwn,Gold or Black without Tracer(colored stripes)		
Insulated Wire(not green)with copper metal conductor	Insulated Wire(not green)with Silver metal conductor		



*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)





Grounding Instructions:

- a) For installation in the United States: Wrap ground wire from outlet box around green ground screw on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.
- b) For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.

Step 4

Push the canopy (F) though the Chain(G) to be locked into ceiling cap





Step 5
Install the bulb (J)

PLEASUE USE ON/OFF TYPE"B" BULB MAX 40-WATT OR CFL BULB MAX 13-WATT THERE IS TYPE "B" 25 WATT BULB IN THE BOX.

Step 6

Consult a qualified electrician to ensure correct branch circuit conductor

ENJOY YOUR LAMP