USER MANUAL FOR MODEL#L405-GBP-203

Thank you for purchasing our product.

For questions or assistance on assembly, parts,

or installation, please contact customer support:

Email service@tiffanydirect.com

Fax 307-633-9603

Please include the product number, order number if any,

and your phone number in the email.

If there are broken or missing parts, please include the part numbers and quantities, and your address. We will ship you the replacement parts.

All emails will be answered within 24 hours. For hard to explain problems, p

lease send us a few pictures showing the problems if you can.

We involve the factory technicians directly in the support, so you can be assured you will deal with the experts


ii. CAUTION

- 1. Rated 110~130V/60Hz, bulb 40W-60W maximum.
- 2. Care should be taken to avoid damage to the surface of lighting and wire, wearing gloves are recommended when installing
- 3. Keep lighting away from acid,alkali and other corrosive chemical or gas, clean the lighting with clean soft cloth only.
- 4. Installation must be carried out by qualified electrician only.
- 5. Disconnect the power before installing, cleaning and replacing lighting.
- 6. Never cover the lighting when power is connected.



The wiring connection luminaire and outlet b

Connect the positive electrode of that is marked, to the positive e outlet box supply wire. Connect electrode of the main wire that negative electrode of the outlet Connect the other negative electrode wire that is unmarked, to the ne outlet box supply wire. Connect to the outlet box ground wire w



SUITABLE FOR THE USE



of ox

of the main wire electrode of the ct the other negative is unmarked, to the t box supply wire. Etrode of the main egative electrode of the the fixture ground wire with wire connectors.

LET BOX
SE SUPPLY and
UND WIRES
E CONNECTORS
EN GROUND SCREW
LET BOX SCREWS

TURE CHAIN
OPY LOCK RING
—FIXTURE LOOP

OR BULB E12 40-60W



INSTRUCTI

