
ASSEMBLY AND INSTALLATION INSTRUCTIONS

C0163

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.


NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. READ AND SAVE THESE INSTRUCTIONS.




Installation Steps

Turn off the power at fuse or circuit box

- Attach two fixture mounting screws to the mounting strap, and then secure it with two lock nuts.
 Adjust the length of the fixture mounting screws if necessary.
- 2. Attach the mounting strap to the outlet box using two mounting screws.
- 3. Screw 7 1/4" long rods and 6 1/4" rods to the other threaded pipes of fixture.
- 4. Pull out the source wires from the outlet box. Make wire connections using wire connectors as follows:
- ---Connect the smooth-coated wire (marked) from the fixture to the black wire from the power source.
- ---Connect the ribbed-coated wire (unmarked) from the fixture to the white wire from the power source.
- ---Attach the fixture grounding wire to the mounting strap with the green grounding screw, and then connect it to the house grounding wire with a wire connector. Carefully put the wires back into the outlet box.
- 5. Attach the fixture canopy to the mounting strap by inserting the fixture mounting screws, and then secure it with two cylinder nuts.
- Install the bulb (not included).Check relamping label at socket area or packaging for maximum allowed wattage.
- 7. Angled mounting recommended for a vaulted or angled ceiling.









Turn on the power at fuse or circuit box

The tollowing parts are available tor re-order it damaged or missing.





1 Year Warranty

Vaxcel warrants all of our products against defects in workmanship and finishes for one year following the date of shipment.

Exclusions: This warranty does not include the failure of products from extreme acts of nature; environmental conditions not suited for the products intended use; operation in temperatures outside of the range specified in the instruction manual; usage with improper power supply, power surges or dips. For coastal locations, some corrosion is considered normal for the environment.

Vaxcel reserves the right to repair, replace or issue a credit for any properly installed product, provided it is returned per RMA instruction. This warranty is limited to the cost of the product only and does not extend to transportation, installation or replacement costs.

How can warranty service be obtained? info@vaxcel.com 1-800-482-9235

