




# BA1753C,PB,AB,ORB,PN,SN,BK

24" Dual Towel Bar





# BA1754C,PB,ORB,SN,AB,BK,PN

Towel Ring



# BA1758C,PB,ORB,SN,AB,PN,BK


Toilet Paper Holder



# KINGSTON BRASS

THE TRADITION OF FINE BRASS

## Dual Towel Bar Installation



### Parts:

Mounting Plate	Mounting Screw & Anchor	Slotted Set Screw
2 Pcs	4 Pcs	2 Pcs

### TOOLS REQUIRED



Flathead Screwdriver



Marking Pencil



Hammer



Power Drill




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

### Installation Steps:

- Step 1. Locate where you would like to install the dual towel bar. Place a base onto the wall and trace around it with a pencil (fig 1).
- Step 2. Unscrew the slotted set screw of the base and remove the mounting plate.
- Step 3. Place the mounting plate in the center of the pencil outline you just made and mark the location of the mounting screws (fig 2). Drill holes at the marked locations (fig 3).
- Step 4. Insert anchors into the holes with a hammer until flush with the wall (fig 4).
- Step 5. Screw the mounting plate (with the lips facing out) to the wall with the mounting screws (fig 5).
- Step 6. Repeat steps 1 through 5 with the other side.
- Step 7. Place the unit, with the small hole in the base underneath, over the mounting plate by tightening the slotted set screws with a flat head screwdriver until the base is tightly fixed (fig 6).


### Cleaning

Clean with a damp cloth only.  
Avoid using metal or abrasive polishes.



# KINGSTON BRASS

THE TRADITION OF FINE BRASS

## Towel Ring Installation



### Parts:

Mounting Plate	Mounting Screw & Anchor	Slotted Set Screw
 1 Pcs	 2 Pcs	 1 Pcs

### TOOLS REQUIRED



Flathead Screwdriver



Marking Pencil



Hammer



Power Drill




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

### Installation Steps:

- Step 1. Locate where you would like to install the towel ring.  
Place a base onto the wall and trace around it with a pencil (fig 1).
- Step 2. Unscrew the slotted set screw of the base and remove the mounting plate.
- Step 3. Place the mounting plate in the center of the pencil outline you just made and mark the location of the mounting screws (fig 2). Drill holes at the marked locations (fig 3).
- Step 4. Insert anchors into the holes with a hammer until flush with the wall (figure 4).
- Step 5. Screw the mounting plate (with the lips facing out) to the wall with the mounting screws (fig 5).
- Step 6. Place the unit, with the small hole in the base underneath, over the mounting plate by tightening the slotted set screw with a flat head screwdriver until the base is tightly fixed (fig 6).


### Cleaning

Clean with a damp cloth only.  
Avoid using metal or abrasive polishes.



# KINGSTON BRASS

THE TRADITION OF FINE BRASS

## Toilet Paper Holder Installation



### Parts:

Mounting Plate	Mounting Screw & Anchor	Slotted Set Screw
 2 Pcs	 4 Pcs	 2 Pcs

### TOOLS REQUIRED



Flathead Screwdriver



Marking Pencil



Phillips Screwdriver



Hammer



Power Drill




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

### Installation Steps:

- Step 1. Locate where you would like to install the toilet paper holder. Place a base onto the wall and trace around it with a pencil (fig 1).
- Step 2. Unscrew the slotted set screw of the base and remove the mounting plate.
- Step 3. Place the mounting plate in the center of the pencil outline you just made and mark the location of the mounting screws (fig 2). Drill holes at the marked locations (fig 3).
- Step 4. Insert anchors into the holes with a hammer until flush with the wall (fig 4).
- Step 5. Screw the mounting plate (with the lips facing out) to the wall with the mounting screws (fig 5).
- Step 6. Repeat steps 1 through 5 with the other side.
- Step 7. Place the unit, with the small hole in the base underneath, over the mounting plate by tightening the slotted set screws with a flat head screwdriver until the base is tightly fixed (fig 6).

### Cleaning

Clean with a damp cloth only.  
Avoid using metal or abrasive polishes.